

7028 Journeyman FLEX Steel

Journeyman FLEX Steel, Climbing, Cross-Over

The Journeyman FLEX Steel continues the tradition of uncompromising performance you've come to rely on every day. New design elements have been incorporated into this jobsite workhorse for improved comfort, durability and reliability. The Journeyman FLEX Steel continues the tradition of keeping your team safe

Features

- Durable alloy steel hardware
- Two D-rings; One Back and One Sternal
- Premium breathable padded air mesh shoulder yoke
- Quick Connect Visi-lock chest buckle
- 18" contoured leg pads
- Low-profile Torso Adjuster and Mating Buckle
- Tongue Buckle Leg Adjusters
- Non-slip dorsal D-ring adjustment

MATERIALS SPECIFICATIONS	
Webbing:	Polyester; Min. 5,000 lbs. tensile strength
Keepers:	Plastic
D-Rings:	Steel; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Steel; Min. 3,375 lbs. tensile strength
Grommets:	Brass
Torsos Adjusters:	Friction
Foam:	High density internal foam

PERFORMANCE SPECIFICATIONS	
Maximum Working Load:	425 lbs.
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES	
Style #	Description
PN 7028	UniFit
PN 7028X/2X	UniFit
For shoulder and waist size ranges, please see Size Charts page.	



7028
Journeyman FLEX Steel

RELEVANT STANDARDS	
ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.