

PRODUCT SPECIFICATIONS

50' DuraTech Cable SRL

#7268SS

Features

- 50' working length.
- Inertial dual disk brake system is efficient and arrest falls quickly and effectively.
- Reduces arrest forces to less than 900 lbs in overhead applications.
- Aluminum alloy construction makes for a rugged and light weight product.

Material Specifications

- Cable:** *3/16", 7X19 Stainless Steel*
- Connectors:** *Stainless Steel; Min. 5,000 lbs. tensile strength*
- Connector Gates:** *Stainless Steel; Min. 3600 lbs. front and side load*

Performance Specifications

- Tensile Strength:** *Min. 3,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *2 feet*
- Average Arrest Force:** *Less than 900 lbs.*
- Max. Elongation:** *Less than 54 inches*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*
Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use in overhead applications - **maximum allowable freefall = 2 feet!**



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.