

PRODUCT SPECIFICATIONS

72706SB1 DuraTech® 6' Mini Web Self-Retracting Lifeline

Features:

- Available in single and twin-leg models
- 6' working length
- Compact and impact-resistant nylon housing
- Integral energy absorber also provides visual indication of fall event
- For use up to 5' below the back D-ring
- Alloy steel swivel eye helps reduce lifeline twisting
- Available with alloy steel, aluminum alloy leg-end and swivel eye connectors including carabiners, snap hooks and rebar hooks.

Materials Specifications	
Webbing:	100% Dyneema®; 4,500 lbs. Min.
Energy Absorber:	Polyester
Swivel Eye:	Alloy Steel, 5/8" hole diameter
SRL Housing:	Nylon 6/6
Main Shaft:	Alloy Steel
Pawls:	Stainless Steel
Connectors:	Aluminum Alloy and Alloy Steel; 5,000 lbs. Min. with 3,600 lbs. Gate Strength

Performance Specifications	
Static Strength:	3,000 lbs. Min.
User Capacity:	310 lbs. Max.
Max. Arrest Distance:	54"
Average Arrest Force:	Less than 900 lbs.
Max. Arrest Force:	1,800 lbs.
SRL Class:	Class B

Relevant Standards	
ANSI:	Z359.14-2014
OSHA:	1926.502 and 1910.66



WARNINGS

- Read, understand and follow all labels and instruction manual prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an energy absorbing lanyard to hip or side D-rings.

Warning: All Fall Protection equipment should only be used after reading and understanding the manufacturer's instructions and proper training on the product. Failure to receive proper training and follow the manufacturer's instructions could result in serious injury or death.