

PRODUCT SPECIFICATIONS

50' Vertical Lifeline

8149

Features

- Anchor-end snap hook and trailing end braided eye.
- 5/8" copolymer-polyolefin rope has a tensile strength of 8,500 lbs.
- Superior resistance to abrasion and UV light.
- Superior hockle resistance.
- Four-tuck splice for superior strength and safety.
- Exclusive steel thimble resist wear and extend the life of the line.



Material Specifications

Rope:	<i>5/8" Copolymer-Polyolefin; Min. 8,500 lbs. tensile strength</i>
Connectors:	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
Thimble:	<i>Alloy Steel</i>
Connector Gates:	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
Max. Capacity:	<i>425 lbs.</i> <i>To maintain ANSI Z359 compliance, limit total user weight to 310lbs</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>A10.32-2004</i> <i>Z359.1-2007</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.