

PRODUCT SPECIFICATIONS

Rebar Positioning Assembly

#8250W

Features

- 2-1/4" gate swiveling rebar hook with two locking snap hooks.
- 1" Polyester webbing complies with the toughest standards in the business.
- To be used with a Full Body Harness equipped with side D-rings for positioning, or a positioning belt with Side D's.

Material Specifications

- Web:** *Polyester - min. strength of 9,800 lbs.*
- Connector:** *Alloy Steel; Min. 5,000 lbs tensile strength*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs. front load and side load*

Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *425 lbs.*
- To maintain ANSI Z359 compliance, limit total user weight to 310lbs*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *Z359.1, A10.32-2004*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- **Maximum freefall is 2 feet - no exceptions .**
- **Must be used with back-up fall arrest - no exceptions .**



**Image shown is 7250W*

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.