

PRODUCT SPECIFICATIONS

Rope Grab Lanyard Set

#8355

Features

- 3' Wrap Pack™ Shock Absorbing Lanyard
- Steel Snap Hook
- Deluxe Self-Tracking/Park Rope Grab
- Self-tracking design provides ease of vertical movement on a 5/8" rope lifeline

Material Specifications

- Webbing:** Polyester; Min. 9,800 lbs. tensile strength
- Energy Absorber:** Polyester; activation greater than 450 lbs.
- Connectors:** Alloy Steel; Min. 5,000 lbs. tensile strength
- Connector Gates:** Alloy Steel; Min. 3,600 lbs. front load and side load

Performance Specifications

- Tensile Strength:** Min. 5,000 lbs.
- Max. Capacity:** 310 lbs.
- Max. Freefall:** 6 feet
- Average Arrest Force:** Less than 900 lbs.
- Max. Elongation:** 48 inches

Relevant Standards

- OSHA:** CFR1926.502, CFR1910.66
- ANSI:** Rope Grab Meets Z359.13-2009

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.