

Derrick/Oil Rig Harnesses

Description_

Custom safety features have been incorporated for extra strength, durability and added comfort for working on derrick/oil rigs. Miller Revolution Derrick harnesses made with DualTech™ webbing and suspension loops.

Materials_

Techweb: Polyester, Nylon **Webbing:** DualTech™

Elastic Keepers: Polyester, Nylon, Elastic

Thread (Stitching): Polyester

D-ring: Clear Chromate Finished Carbon Steel,

Extended 18in (457mm)

Buckles: Clear Chromate Finished Carbon Steel

Grommets: Brass **Labels:** Valeron

Cam Buckle: Glass-filled Nylon, Aluminum, Stainless

Steel

Pivotlink: Clear Chromate Finished Carbon Steel,

Stainless Steel

Back, Belt, Shoulder

Pads: Nylon, Polyester, Urethane

Label Pack: Evoprene, Nylon

Technical.

Max. Working Load:400lbs (181.4kg)Webbing Min.Tensile:5000lbs (22kN)D-ring Min. Tensile:5000lbs (22kN)



Certification

Meets or exceeds all OSHA, ANSI and CSA requirements.

Model	Description
	Back D-ring w/18" extension, side and back positioning D-rings & pad on floating belt, quick-connect buckle legs, shoulder pads. Accepts soft abdomen pad (RIA-P6/).
RDTSLP4-QC-FBDP/UBK	Back D-ring w/18" extension, side and back positioning D-rings & pad on floating belt, quick-connect buckle legs, shoulder pads. Accepts rigid abdomen pad w/carabiner connections for a safety rope (RIA-P4/).
850-OIL/LYL	"Bellybuster" harness with permanently-attached belt; rigid abdomen pad; built-in auto-lock carabiners (originally model #970130)
850DT-OIL-RS/LAG	Combination "bellybuster" harness with permanently-attached belt; rigid abdomen pad; built-in auto-lock carabiners; built-in sling seat for raising/lowering (originally model #000217)

