

PRODUCT SPECIFICATIONS

Confined Space Tripod

#7275

Features

- Adjustable height 6' - 11'.
- Tripod head features one integral pulley and three additional anchor-points for use with 3-way SRL's and confined space winches.

Material Specifications

Head: *Aluminum alloy; Min. 3,600 lbs.*

Legs: *Aluminum - unrated.*

Performance Specifications

Static Strength: *Min. 3,000 lbs.*

Max. Capacity: *310 lbs.*

Max. Freefall: *N/A*

Average Arrest Force: *N/A*

Max. Elongation: *N/A*

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*

ANSI: *A10.32-2004*

Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use in overhead applications - **maximum allowable freefall = 2 feet!**



WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.